

PATENT APPLICATION

ATTORNEY DOCKET NO.: CBZ-0187

TITLE OF THE INVENTION

DRAFTING DEVICE WITH TWIN TOP DELIVERY

ROLLERS SURROUNDED BY APRONS

FIELD OF THE INVENTION

The invention relates to a drafting device with twin top delivery rollers in which the aprons are guided around deflection members arranged on the area facing away from the clamping surface of the front roller pair.

BACKGROUND OF THE INVENTION

When drafting slivers in drafting devices, the clamping action of the roller pairs plays a decisive part for the transmission of the drafting forces onto the fiber bundle. The roller pairs of a drafting device therefore consist of a lower, channeled steel roller, the so-called bottom roller, and of an upper roller, the so-called top roller, that is pressed by a loading apparatus onto the bottom roller. This top roller generally has an elastic coating so that no clamping line is produced but rather a clamping surface by the deformation of the elastic coating, which surface brings about a distinctly better retention of the fibers. A good clamping action is exerted on the fiber bundle without damaging the fibers. Experience has shown that soft roller coatings therefore yield better drafting results since the softer the coating is, the larger the clamping action is. However, the soft roller coatings have the disadvantage that they wear very rapidly and must be reground. This changes the geometry of the drafting cylinder and therewith also the properties of the coating,

which for its part has a disadvantageous effect on the drafting conditions and thus on the yarn quality. Moreover, the grinding of the roller is an expensive measure.

In order to unite a high degree of softness of the roller coating with high wear resistance and thus create optimal drafting conditions for a long time of use, DE 102 60 025.2 (that is not a prior publication) suggests surrounding a top roller with a soft coating with an apron with a high wear resistance. This separate apron has the advantage that it can be readily replaced in the case of wear or damage. A replacement by an apron with a different hardness, a different method, or some other different type or quality, is readily possible.

It is obvious that this solution is advantageous, in particular on the front roller pair of a drafting device in which the rollers run especially rapidly and have the greatest influence on a reliable drafting.

The surrounding of the top front rollers of drafting devices with aprons is known (DE 816 069; DE-GM R7). The explained purpose of these rather long aprons is to prevent the formation of windings around the top rollers of the front roller pair. These aprons are associated with tensioning devices that keep them under tractive tension and thus keep them tight.

The aprons are conducted on these tensioning devices via stationary deflection members. It turned out that drive energy is consumed by the aprons being drawn over these deflection members, the aprons experience a braking that has a disadvantageous effect on the drawing process and are subject to wear.

The present invention therefore has the problem of avoiding these disadvantages.

SUMMARY

Objects and advantages of the invention are set forth in part in the following description, or may be obvious from the description, or may be learned through practice of the invention.

In order to keep the tractive tension as low as possible in the aprons, aprons are therefore used that have the tendency to assume an approximately circular form in the non-loaded state in the circumferential direction. Since the aprons generally consist of synthetic material, this tendency is a given inherent feature. The interval between the top front rollers and the bearing surfaces of the deflection members is selected in such a manner that the aprons can bulge out in the areas between top roller and deflection member due to the tendency to assume an approximately circular form in the circumferential direction. They then rest on the deflection members with only a slight pressure and accordingly are under only a slight tractive tension. They therefore experience practically no braking, consume no noticeable drive energy and are subject to practically no wear.

This effect is favored even more if the coefficient of friction between the inner running layer of the aprons and the deflection members is kept as low as possible by an appropriate pairing of material.

The low contact pressure of the aprons on the deflection members can then be achieved if the circumference of the circular form striven for corresponds approximately to $1\frac{1}{2}$ to 3 times the circumference of the surrounded top rollers and if the interval between the surrounded top rollers and the deflection members corresponds to one half to twice the diameter of the surrounded top rollers.

In this instance the two deflection members of a twin top roller can be formed on a one-piece, rigid, holder fastened on a structural component connected to the twin top roller in a preferably detachable manner. The holder can comprise a holding member that can be connected to the shaft of the twin top roller or it can be fastened to the guide rod of the twin top roller or to the top roller carrying and loading arm.

Guiding surfaces are arranged for the lateral guidance of the aprons.

Two preferred non-limiting exemplary embodiments of the invention are shown in the figures of the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a front view of a drafting device in a first embodiment of the invention in section in plane A-A.

Figure 2 shows a lateral view of the subject matter of figure 1.

Figure 3 shows another possibility of fastening a holder in a front view.

Figure 4 shows a lateral view of the subject matter of figure 3.

DESCRIPTION

Reference will now be made to embodiments of the invention, one or more examples of which are illustrated in the drawings. Each embodiment is presented by way of explanation of the invention, and not as a limitation of the invention. For example, features illustrated or described as part of one embodiment may be used with another embodiment to yield still a further embodiment. It is intended that the invention include these and other modifications and variations of the embodiments described herein.

An embodiment of the invention relates to a drafting device of a common design with a steel front bottom roller 1 running the length of the drafting machine, on which top roller pairs 2 rest, of which only one is shown here in the front view of figure 1. The two top rollers 3, 4 of the top roller pairs comprise a preferably soft coating 5 in order to achieve the initially described advantageous drafting conditions. They are connected by shaft 6 clipped onto spring-loaded guide rod 7. Guide rod 7 is arranged on a top roller carrying and loading arm (not shown).

One-piece holders 8 preferably manufactured from die casting are provided from which two deflection members 9 project laterally, over which aprons 10, 11 that also surround top rollers 3, 4 run. These deflection members 9 have deep deflection (i.e. "turn-around") surfaces 12 that are limited by collars 13, 14 and thus prevent the aprons from running off laterally from top rollers 3, 4 when the drafting device is running.

As can be recognized from the bulging of aprons 10, 11 in figure 2 between top rollers 3, 4 and deflection members 9, they are placed only loosely around the deflection members and are accordingly only under the slight pressure that is caused solely by the tendency of the aprons to assume a circular form in the circumferential direction.

It is sufficient for the mode of action of the aprons striven for if they have a circumference corresponding to approximately $1\frac{1}{2}$ the circumference of top rollers 3, 4. The interval "a" (Fig. 4) between the axis of rotation of the top rollers and between surfaces 12 of deflection members 9 corresponds approximately to the diameter of the top rollers. However, the circumference of the aprons can also be

increased to approximately 3 times the circumference of the top rollers, or in some instances even further, in which case interval a, shown in figure 4, between the axis of rotation of the top rollers and surfaces 12 of deflection members 9 should be increased to at least approximately twice the diameter of the top rollers. It is understood that interval a must be in an appropriate relationship to the circumference and also to the stiffness of aprons 10, 11. In the case of rather stiff aprons interval "a" should be reduced.

Holders 8 of the embodiment of figures 1, 2 comprise two holding members 15 that can be clipped onto shaft 6 of the associated top roller pair 2 and that guide the holders. Thus, a device can be readily removed from a guide rod 7 if an exchange of top rollers 3, 4 or of aprons 10, 11 is required. To this end, shaft 6 is clipped downward out of the guide rod and holding members 15 are pivoted away from the shaft to the front. When the drafting device is running, holders 8 tend to rotate clockwise with top rollers 3, 4 in the lateral view of figure 2. In order to prevent this, systems are provided that can be formed in the simplest form by the upper sides of guide rods 7, on which the middle range 16 of holders 8 rests.

In the embodiment of figures 3, 4 holders 8 can be clipped onto guide rods 7 by resilient clamps 17 connected to the holder. In this instance, holders 8 are already held in such a manner that they rotate in unison.

As is not shown in detail, holders 8 can also be articulated to the top roller carrier and loading arms. In this instance they can be set, e.g., into the holders of the upper cleaning rollers, that are generally no longer required when using the surrounding aprons.

Aprons 10, 11 preferably consist of at least two layers of which the outer layer making contact with the fibers is adapted to the requirements of a good fiber clamping and low wear and the inner layer running over surfaces 12 of deflection members 9 is adapted to the requirement of a low-friction running.

It should be appreciated by those skilled in the art that the invention includes modifications and variations to the embodiments described herein.